

SimplyBRANDS cable selector guide will assist with your **SimplyBRANDS** selection process to easily identify the correct cable required to properly support the bandwidth, transmission rate & PoE requirements that your installed devices & applications need to perform at the highest level.

All Series
Available in 9 colors

- BK=Black
- BL=Blue
- GY=Gray
- GN=Green
- OR=Orange
- PUR=Purple
- RD=Red
- WT=White
- YL=Yellow



SimplyCABLE™
PRO SERIES



SimplyCABLE™
PRO SERIES



SimplyCABLE™
INSTALLER SERIES











SimplyCABLE™
STANDARD SERIES

Category Type	Cat6a	Cat6	Cat6	Cat6
Part Number Series	SC-BC3700XX	SC-BC3600XX	CAT6-XX-ETL	SC-BC1600XX
MSRP	\$315.95	\$254.95	\$229.95	\$188.95
QR Code				
Cable Construction	U/UTP	U/UTP	U/UTP	U/UTP
Jacket Material/Rating	PVC-UV	PVC-UV	PVC	PVC
Fire Safety Rating	CMR FT4	CMR FT4	CMR FT4	CMR FT4
3rd Party Rated	UL c(UL)	UL c(UL)	ETL c(ETL)	ETL c(ETL)
Installation Type	Indoor/Outdoor UV Sun Res	Indoor/Outdoor UV Sun Res	Indoor	Indoor
Tested Bandwidth	650 MHz	600 MHz	575 MHz	550 MHz
ISO/IEC 11801 Class Type	Class Ea	Class E	Class E	Class E
Transmission Standards	10G+	10G	8G	1G
PoE Rating	90W Type 4	60W/90W Type 3-4	30W/60W Type 2-3	15W/30W Type 1-2
Wire Conductors	Solid BC	Solid BC	Solid BC	Solid BC
Wire AWG	23 AWG	23 AWG	23 AWG	23 AWG
Conductor Insulation	HDPE	HDPE	HDPE	HDPE
Pair Separator/Spline	Yes	Yes	Yes	Yes
Cable Overall Diameter OD	7.2mm (0.283 in)	6.3mm (0.248 in)	6.2mm (0.244 in)	6.0mm (0.236 in)
Insulated Conductor OD	1.05mm (0.041 in)	1.05mm (0.041 in)	1.0mm (0.039 in)	0.99mm (0.038 in)
Packaging Type	Premium Reel-in-Box	Premium Reel II Box	Reel II Box	Reel II Box
Packaged Length (ft/m)	1000ft/305m	1000ft/305m	1000ft/305m	1000ft/305m
20 Free Connectors	S45-1720P	S45-1620P	-	-

Applications

Higher rated cables are backwards compatible to lower rated cables.



SimplyCABLE™

PRO SERIES



Higher
Copper Content



Highest
Bandwidth



Higher
PoE Performance



Reelix II
No Tangle Box



Indoor/Outdoor
UV Sun-Res



25 Year Certified
System Warranty



Limited
Lifetime Warranty



UL
Rated

PREMIUM BOX FEATURES

Application Icons
by Cable Type

Graphic Rich
Features Icons



20 Free Connectors
Inside Every Box

Cat6a Reel in Box
Cable Dispenser

Color Coded

To Visually Reinforce
Category Cable Type

- CAT5E
- CAT6
- CAT6/6A
- CAT6A/7/7A

Cat5e/6 Reelix II
Easy to Pull
Cable Dispenser

Wire Termination
Guide

Compatible Products
Panel

Free Connectors Recommended Crimp Tool



S45-C101